



SIGNMAKER SOLUTIONS

## INSTRUCTIONS FOR THE APPLICATION OF LARGE SELF ADHESIVE VINYL DECALS

1. **Important!** Using **methylated spirits** clean, dry and remove all dirt, grease and silicon residue from the surface that the decal will be applied to.
2. Mark the decal level position with a felt tipped pen / masking tape.
3. Spray a light film of mild soapy water on area to be applied to. (one drop of liquid soap per 1 litre – no more).
4. Peel off the decal from it's backing sheet & apply to the wet surface.
5. Move the decal to the required position.
6. Stand back a few metres and check that it looks correct.
7. Using a credit card covered with cloth or similar piece of blunt plastic to act as a squeegee, apply pressure to the centre of the decal stroking from the centre out to the edge moving any trapped air bubbles.
8. Gently dry and remove any excess water with a soft cloth.
9. Allow to dry for a minimum of 30 minutes.

Any remaining air bubbles may then be removed by pricking the bubbles with a sharp pin and smoothing out the Decal with the cloth covered squeegee.

Signmaker Solutions  
Help line : [02 9905 5323](tel:0299055323)

6 Sydenham Road Brookvale NSW 2100  
Telephone: 02 9905 5323 Facsimile: 02 9905 9211  
Email: [sales@signmaker.com.au](mailto:sales@signmaker.com.au) Web Site: [www.signmaker.com.au](http://www.signmaker.com.au)  
Incorporating Magna Ad Signs

Goldorme Pty Limited(Inc.in NSW) ACN 003 879 669 **ABN 72 003 879 669**

MEMBER OF STATE CHAMBER OF COMMERCE